



UPS ELITE 1000VA **Pro Smart**

- LCD display
- Real capacity 1000VA
- Wide input voltage range (162~290VAC)
- Compatible with generators
- Overload protection
- Short circuit protection
- Built-in AVR
- Battery deep discharge protection & overcharge protection.

SPECIFICATION

Capacity	1000VA/600W
Input	
Voltage Range	162~290Vac
Nominal Frequency	50/60Hz
Output	
On Battery Output Voltage	Simulated Sine Wave 230Vac z+/-10%
On Battery Output Frequency	50/60 Hz+/-1%
Overload Protection	Breaker/Fuse
Physical	
Dimensions(W x H x D)	96mm x 138mm x 286mm
Battery	
Sealed Maintenance Free Lead Acid Battery	12V/9AH x1
Typical Recharge Time	8 Hours
Warning Diagnostics	
Indicators	Power On/ Using Battery
Audible Alarms	On Battery, Low Battery, Overload, Fault
Environmental	
Operating Temperature	0°C to 40°C
Operating Relative Humidity	0 to 90%
Management	
Auto-Charger	Yes
Auto-Restart	Yes
USB COMM. Port	Yes



LED INDICATOR AND ALARM

LED STATUS		
Normal	LED lighting	Off
Battery Discharge	LED lighting	Beep once every 30 seconds
Battery Low	LED lighting	Beep once every 2 seconds
Overload	LED lighting	Beep once every 0.5 seconds
Off charging mode	LED off	Off
Fault	LED off	Continuous alarm