

ELITE 7.5

Sealed Rechargeable Battery

Features


Compact design
Heavy duty grids
Maintenance free
Low self-discharge
Wide operating temperature
High impact resistive plastic cast



120)

MODEL	
Nominal Voltage	12V
INPUT	
Rating Capacity	20 Hour Rate 0.375A/7.5AH / 10 Hour Rate 0.69A/6.9AH / 5 Hour Rate1.20A/6.0AH / 1 Hour Rate 4.50A/4.5AH
CURRENT	
Max Discharge Current	112.5A (5S)
CHARGE	
Constant Voltage	Cycle: Initial charging less than 2.25A / Float: Voltage 14.4-14.7V/77°F (25°C), Voltage 13.5-13.8V/77°F (25°C)
INTERNAL RESISTANCE	
Fully Charged Battery	24ΜΩ
SELF DISCHARGE (77°F 25°C)	
Capacity after 3 Months Storage	91%
Capacity after 6 Months Storage	81%
Capacity after 12 Months Storage	60%
TERMINAL	
Terminal	F1/F2
PHYSICAL	
Dimension W x D x H (mm)	152 x 65 x 95
Net Weight (kgs)	2
Packaging type	5pcs per Carton Mercury

^{*}Specifications are subject to change without prior notice.



5 pcs in a Carton

