

TALL TUBULAR
BATTERY
 ELITE 220Ah



Features

Compact design
 Heavy duty grids
 Low Maintenance
 Low self-discharge
 Wide operating temperature

High impact resistive plastic cast
 In-line level indicator for easier access
 Tower type PPCP container-cover design
 Special envelope separator to minimizes internal short circuit
 Tubular plate design specifically tailored for deep cycle usage

Battery Construction								
Component	Positive Plate	Negative Plate	Container	Cover	Vent Plug	Terminal	Separator	Electrolyte
Material	Lead Dioxide	Lead	PPCP	PPCP	PPCP	Lead Alloy	Poly Ethylene	Dilute Sulfuric Acid

Technical Specifications						
Nominal Voltage	C20 Capacity at 27C till 10.5V (Test Gravity 1.240 +/- 0.005)*		Overall Dimensions			Filled Wt
			Length	Width	Height up to float top	
(Volt)		(Ah)	+/-3MM	+/-3MM	+/-3MM	+/-5% Kg
		220	503	189	441	62.0

Constant Power discharge performance**					
Load	500W	400W	300W	200W	100W
Maximum Duration	2 Hours 45 Minutes	4 Hours 05 Minutes	5 Hours 40 Minutes	8 Hours 50 Minutes	20 Hours 55 Minutes