



UPS Elite 1000 Pro

Line Interactive UPS

- Built-in AVR with wide input range of 140~300VAC
- DC Start
- Auto Restart
- Wide Range of Input Frequency
- Output Short Circuit Protection
- Over Temperature Protection
- Overload Protection
- Telephone / Modem Line Protection

Specifications

Model	Elite 1000 Pro
Capacity	1000VA
Input	
Rating Voltage	220-240VAC
Voltage range	140-300VAC
Frequency	50/60Hz
Current	4.8A Max.
Output	
Voltage regulation (Batt. Mode)	±10%
Frequency	50/60Hz
Frequency regulation (Batt. Mode)	±1Hz
Waveform	Simulated sine wave
Output sockets	2 x Universal
Battery	
Battery Type	Sealed lead acid, maintenance free
Nominal voltage (VDC)	12VDC
Number x Capacity (Ah) of battery	1 x 12V/9Ah
Battery recharge time	6-8 hours to 90% after complete discharge
Transfer time	Typical 8ms, 15ms Max
Protection	Short circuit, Overcharge, Overload, Over discharge
General	
Physical Dimension (LxWxH)	162 x 95 x 319mm
Enclosure/protection	IP20(dustproof but not waterproof)
Environment	
Operating temperature	0-40 °C
Noise Level (1M)	Less than 45dB
Maximum relative humidity	0-90%(non - condensing)

