

ELITE 1000 PRO SMART

Line Interactive UPS



Built-in AVR

Stabilizes Output Voltage and enhances Battery life as UPS works on main mode on very High or Low Voltage Conditions.

Green Power Function

Our UPS is equipped with Green Power Function. For saving power and protecting Battery, the method of Deep Discharging Protection is adopted on Inverter mode.

Audible Alarm

Audible Alarm for Backup / Low Battery / Overload Mode.

Line Interactive UPS

LCD display

Real capacity 1000VA

Wide input voltage range (162~290VAC)

Compatible with generators

Overload protection & Short Circuit protection

Built-in AVR

Battery deep Discharge protection
& Overcharge protection.

ELITE 1000 PRO SMART

Line Interactive UPS



SPECIFICATION

Capacity	1000VA/600W
Input	
Voltage Range	162~290Vac
Nominal Frequency	50/60Hz
Output	
On Battery Output Voltage	Simulated Sine Wave 230Vac z+/-10%
On Battery Output Frequency	50/60 Hz+/-1%
Overload Protection	Breaker/Fuse
Physical	
Dimensions(W x H x D)	96mm x 138mm x 286mm
Battery	
Sealed Maintenance Free Lead Acid Battery	12V/9AH x1
Typical Recharge Time	8 Hours
Warning Diagnostics	
Indicators	Power On/ Using Battery
Audible Alarms	On Battery, Low Battery, Overload, Fault
Environmental	
Operating Temperature	0°C to 40°C
Operating Relative Humidity	0 to 90%
Management	
Auto-Charger	Yes
Auto-Restart	Yes
USB COMM. Port	Yes

LEDS INDICATOR AND ALARM

LED STATUS		
Normal	LED lighting	Off
Battery Discharge	LED lighting	Beep once every 30 seconds
Battery Low	LED lighting	Beep once every 2 seconds
Overload	LED lighting	Beep once every 0.5 seconds
Off charging mode	LED off	Off
Fault	LED off	Continuous alarm

