



# UPS Elite 1200 Pro

- Wide Input Voltage Range
- Compatible with Generator
- Overload Protection
- Short Circuit Protection
- Built-in AVR
- Battery deep discharge protection & Overcharge Protection

## Specifications

<b>Model</b>	<b>Elite 1200 Pro</b>
<b>Capacity</b>	1200VA
<b>Input</b>	
Rating Voltage	220-240VAC
Voltage range	140-300VAC
Frequency	50/60Hz
Current	6.0A Max.
<b>Output</b>	
Voltage regulation (Batt. Mode)	±10%
Frequency	50/60Hz
Frequency regulation (Batt. Mode)	±1Hz
Waveform	Simulated sine wave
Output sockets	4 x Universal
<b>Battery</b>	
Battery Type	Sealed lead acid, maintenance free
Nominal voltage (VDC)	24VDC
Number x Capacity (Ah) of battery	2 x 12V/7.5Ah
Battery recharge time	6-8 hours to 90% after complete discharge
<b>Transfer time</b>	Typical 4-8ms, 13ms Max
<b>Protection</b>	Short circuit, Overcharge, Overload, Over discharge
<b>General</b>	
Physical Dimension (LxWxH)	338 x 149 x 162mm
Enclosure/protection	IP20(dustproof but not waterproof)
<b>Environment</b>	
Operating temperature	0-40 °C
Noise Level (1M)	Less than 45dB
Maximum relative humidity	0-90%(non - condensing)

