

ELITE 1500 PRO

Line Interactive UPS



FEATURES

- Built-in AVR
- Wide input voltage range
- Compatible with Generator
- Intelligent Battery Management
- Overload protection
- Short circuit protection
- Overcharge protection.
- Battery deep discharge protection



ELITE 1500 PRO

Line Interactive UPS



SPECIFICATIONS

Capacity	1500VA
INPUT	
Rating Voltage	220-240VAC
Frequency	50/60Hz
Current	7.2A Max
Power Cord	Built-in Cable with fuse
OUTPUT	
Waveform	Battery Mode (Simulated sine wave) AC Mode (Synchronize with Input)
Power Factor	0.6
Rating Voltage	220-240VAC
Output Range	220VAC - 10% to + 10% (Battery Mode)
Output sockets	4 x Universal - Battery Backup
BATTERY	
Battery Type	Sealed lead acid, maintenance free
Nominal voltage (VDC)	24VDC
Number x Capacity (Ah) of battery	1 x 12V/8.2Ah
Battery recharge time	6-8 hours to 90% after complete discharge
Transfer time	Typical 4-8ms, 13ms Max
Protection	Short circuit, Overcharge, Overload, Over discharge
Communication Interface	NO
GENERAL	
Physical Dimension (LxWxH)	353 x 149.3 x 162mm
Enclosure/protection	IP20 (dustproof but not waterproof)
Net Weight	8.7Kgs
ENVIRONMENT	
Operating temperature	0-40 °C
Noise Level (1M)	Less than 45dB
Maximum relative humidity	0-90% (non - condensing)

