



UPS Elite2000Pro

- Built-in AVR
- Wide Range of Input Voltage
- Overload and Short Circuit Protection
- Compatible with Generator
- Battery Deep Discharge Protection & Overcharge Protection

Specifications

Model	Elite 2000 Pro
Capacity	2000VA
Input	
Rating Voltage	220-240VAC
Voltage range	140-300VAC
Frequency	50/60Hz
Current	9.0A Max.
Output	
Voltage regulation (Batt. Mode)	±10%
Frequency	50/60Hz
Frequency regulation (Batt. Mode)	±1Hz
Waveform	Simulated sine wave
Output sockets	4 x Universal
Battery	
Battery Type	Sealed lead acid, maintenance free
Nominal voltage (VDC)	24VDC
Number x Capacity (Ah) of battery	2 x 12V/9Ah
Battery recharge time	6-8 hours to 90% after complete discharge
Transfer time	Typical 4-8ms, 13ms Max
Protection	Short circuit, Overcharge, Overload, Over discharge
Communication Interface	NO
General	
Physical Dimension (LxWxH)	225 x 125 x 390mm
Enclosure/protection	IP20(dustproof but not waterproof)
Environment	
Operating temperature	0-40 °C
Noise Level (1M)	Less than 45dB
Maximum relative humidity	0-90%(non - condensing)

