



UPS Elite**2000U**SMART

- LED display
- Real capacity 2000VA
- Wide input voltage range (140V-300VAC)
- Compatible with generators
- Overload protection
- Short circuit protection
- Built-in AVR
- Battery deep discharge protection & overcharge protection.

Specifications

| | |
|-----------------------------------|---|
| Model | Elite 2000U Pro |
| Capacity | 2000VA |
| Input | |
| Rating Voltage | 220-240VAC |
| Voltage range | 140-300VAC |
| Frequency | 50/60Hz |
| Current | 9.0A Max. |
| Output | |
| Voltage regulation (Batt. Mode) | ±10% |
| Frequency | 50/60Hz |
| Frequency regulation (Batt. Mode) | ±1Hz |
| Waveform | Simulated sine wave |
| Output sockets | 4 x Universal |
| Battery | |
| Battery Type | Sealed lead acid, maintenance free |
| Nominal voltage (VDC) | 24VDC |
| Number x Capacity (Ah) of battery | 2 x 12V/9Ah |
| Battery recharge time | 6-8 hours to 90% after complete discharge |
| Transfer time | Typical 4-8ms, 13ms Max |
| Protection | Short circuit, Overcharge, Overload, Over discharge |
| Communication Interface | USB/RJ11 |
| General | |
| Physical Dimension (LxWxH) | 225 x 125 x 390mm |
| Enclosure/protection | IP20(dustproof but not waterproof) |
| Environment | |
| Operating temperature | 0-40 °C |
| Noise Level (1M) | Less than 45dB |
| Maximum relative humidity | 0-90%(non - condensing) |

