



TRUSTED PERFORMANCE
TRUSTED PARTNER

MH110GT

MOTHERBOARD



Chipset

Intel H110 Express Chipset

CPU

Supports 6/7/8th(SKYlake). Intel 14nm CPUs (LGA1151)

Memory

2*240-pin DDR4 SDRAM slots, Memory up to 32GB,
Supports Dual channel DDR4 1600/1866/2133/2400MHZ

LAN

Realtek 10/100Mbps LAN on board

Sound

Realtek ALC 6-CHANNEL HD Audio Codec
onboard provides front audio and mic interface and
front stereo mic interface

I/O Interface

4x USB 2.0, 2x USB 3.0, 1x VGA port, 1xHDMI port,
1x RJ45 port,1x 3-in-1 Audio port(line in/line out/MIC in)

SATA

4XSATA3.0, Experience Doubled Transfer
speed of with 3rd generation SATA interface
running at 6.0GB/s.

HDMI

High-definition multimedia interface able to provide
upto 5Gb/s video transmitting bandwidth & 8-channel
high quality audio all through a single cable

Expansion

1x PCI Express Slot x 16 slot
1x PCI Express Slot x 1 slot, 1x Nvme-M.2 Connector

Onboard Interface

1x 24-pin ATX power connector
1x 4-pin ATX 12V power connector
2x USB connector, can support 2*USB 2.0
& 2*USB 3.0, 1x F-AUDIO connector,
1x F-PANEL connector, 1x F-SPEAKER connector
1x FAN connector , 1x LPC-DEBUG connector



TRUSTED PERFORMANCE
TRUSTED PARTNER

MH110GT

MOTHERBOARD



Specifications



| | |
|-------------------|--|
| CPU | Supports 6/7/8th(SKYLake). Intel 14nm CPUs (LGA1151) |
| Chipset | Intel H110 Express Chipset |
| Memory | 2*240-pin DDR4 SDRAM slots Memory up to 32GB Supports dual channel DDR4 1600/1866/2133/2400 MHZ |
| I/O interface | 4xUSB2.0 2xUSB 3.0 1x VGA port 1x HDMI port 1x RJ45 port 1x 3-in-1 Audio port(line in/line out/MIC in) |
| Onboard interface | 1x 24-pin ATX power connector 1x 4-pin ATX 12V power connector 2x USB connector, can support 2*USB 2.0 & 2*USB 3.0 1x F-AUDIO connector 1x F-PANEL connector 1x F-SPEAKER connector 1x FAN connector 1x LPC-DEBUG connector |
| Integrated sound | Realtek ALC 6-channel HD Audio Codec onboard provides front audio interface provides front stereo mic interface |
| Storage | 4 x SATA 3.0 (6GB/s) ports |
| Integrated lan | Realtek 10/100 Mbps LAN onboard |
| Expansion slot | 1x PCI Express x16 slot,1x PCI Express x1 slot 1x NVME-M.2 connector |
| Dimension | Micro-ATX architecture(17*19 cm) |