



# TRUSTED PERFORMANCE TRUSTED PARTNER





### Chipset



Intel H81 Express Chipset

### **CPU**



Supports 5/4th Gen (HASWELL) Intel 22nm CPUs (LGA1150)

### Memory



2\*240-pin DDRIII SDRAM slots, Memory up to 16GB, Supports dual channal DDR3 1066/1333/1600 MHZ

### LAN



Realtek 10/100Mbps LAN on board

### Sound



Realtek ALC662 6-CHANNEL HD Audio Codec onboard provides front audio and mic interface

### I/O Interface



4x USB 2.0, 2x USB 3.0, 1x VGA port, 1xHDMI port, 1x RJ45 port, 1x 3-in-1 Audio port(line in/line out/MIC in)

### SATA



2XSATA3.0 (6GB/s), 2 x SATA 2.0 (3GB/s) ports. Experience Doubled Transfer speed of with 3rd generation SATA interface running at 6.0GB/s.

### **HDMI**



High-definition multimedia interface able to provide upto 5Gb/s video transmitting bandwidth and 8-channel high quality audio all through a single cable

### **Expansion**



1x PCI Express Slot x 16 slot 1x PCI Express Slot x 1 slot, 1x Nvme slot

### **Onboard Interface**



1x 24-pin ATX power connector

1x 4-pin ATX 12V power connector 2x USB connector, can support 4\*USB 2.0

1x F-AUDIO connector / 1x F-PANEL connector

1x F-SPEAKER connector / 1x FAN connector

1x LPC-DEBUG connector





# TRUSTED PERFORMANCE TRUSTED PARTNER

# MH81NT MOTHERBOARD



## Specifications









CPU	Intel 22nm CPUs (LGA1150)"
	• • •
Chipset	Intel H81 Express Chipset
Memory	2*240-pin DDR III SDRAM slots
	Memory up to 16GB
	Supports dual channal DDR3 1066/1333/1600 MHZ
I/O interface	4xUSB2.0
	2xUSB3.0
	1x VGA port
	1x HDMI port
	1x RJ45 port
	1x 3-in-1 Audio port(line in/line out/MIC in)
Onboard interface	1x 24-pin ATX power connector
	1x 4-pin ATX 12V power connector
	2x USB connector, can support 4*USB 2.0 1x F-AUDIO connector
	1x F-AODIO connector
	1x F-SPEAKER connector
	1x FAN connector
	1x LPC-DEBUG connector
Integrated sound	Realtek ALC 6-channal HD Audio Codec onboard
	provides front audio interface
	provides front stereo mic interface
Storage	2 x SATA 2.0 (3GB/s) ports,2 x SATA 3.0 (6GB/s) ports
Integrated lan	Realtek 10/100 Mbps LAN onboard
Expansion slot	1x PCI Express x16 slot
'	1x PCI Express x1 slot
	1x NVME slot
Dimension	Micro-ATX architecture(17*19cm)