



MAVERICK 750

Line Interactive UPS

BUILT-IN AVR

Stabilizes output voltage and enhances battery life as UPS works on main mode on very high or low voltage conditions.

GREEN POWER FUNCTION

Our UPS is equipped with green power function. For saving power and protecting battery, the method of deep discharging protection is adopted on inverter mode.

AUDIBLE ALARM

Audible alarm for backup / low battery / overload mode.





MAVERICK 750

Line Interactive UPS

SPECIFICATIONS

Capacity | 650VA / 360W

INPUT

Nominal Voltage | 230VAC
Nominal Frequency | 50/60Hz

OUTPUT

On Battery Output Voltage | 230±10%Vac
On Battery Output | 50/60 Hz+/-1%
Overload Protection | Software

BATTERY

Sealed Maintenance Free | 12V / 7AH x 1
Lead Acid Battery
Typical Recharge Time | 8 Hours

PHYSICAL

Dimensions D x W x H (mm) | 87 x 165 x 276
Net Weight (kgs) | 4.01Kg

ENVIRONMENT

Operating Temperature | 0°C to 40°C
Operating Relative Humidity | 0 to 90%

LEDS INDICATOR

LED	ALARM	CONDITION
On	Off	Normal
Flash	Beep 1 time In Every 30 Seconds	Utility Failure-The UPS is providing battery power to outlets.
Flash	Beep 1 time In Every 2 Seconds	Utility Failure-The UPS is providing battery power. The rapid beeps indicate the battery will run out of power shortly.
Flash	Beep 1 time In Every 0.5 Second	Overload-Occurs when connected equipment exceeds the rating of the unit. Turn the UPS off and unplug at least one piece of equipment from the UPS.



FEATURES

Compact size and Light Weight .

Microprocessor Control guarantees high reliability.

Equipped with Boost and Buck AVR.

Green Power Function for Energy Saving.

DC Start Function.

Auto restart while AC recovery.

Provides AC Overload protection.

